種 別 Type	品 名 Model	シャフト Shaft	変化特性 Taperd curve	抵抗值 Resistance value 100 200 300 500 101 201 301 501 102 202 302 502 103 203 303 503 104 204 254 304 504 105 205																				
				100 200	300 500	101	201	1 301	501	102	202	2 30	2 502	2 103	203	3 303	503	104	204	25	54 30	04 50	4 10	5 20!
	RV16YN	10S	В																	1				
	RV16YN	15S	В																					
	RV16YP	10S	В																					
炭素系混合体	RV16YP	15S	В																	1				
可変抵抗器	RV24YN	15S	В																					
Carbon Composition	RV24YN	20S	A				1	1	1		1	1							1					
	RV24YN	20S	В																					
	RV24YNME	20S	В				1	1	1											1				
	RV24YG	20S	В				1	1				1				1				1)
	RV30YN	15S	В																	1				
	RV30YN	20S	В																	1				
	RV30YNME	20S	В				-		-		1	1			-	1								
低電力巻線形 可変抵抗器	RA25Y	15S	В					1							1	1	-			1		ł		
	RA25Y	20S	В					1								1				1				
Low power	RA30Y	15S	В					-							1				-					
Wire wound	RA30Y	20S	В					1							1	1	-			1		ł		
	G32A	-	В																	1				
	G32AT	-	В																					
	G32B	-	В																	1				
	G32BT	-	В																	1				
	G43A	-	В					-				-				1					1			
	G43B	-	В					-				1				1				1				
	G43AT	-	В					1				1				1				1				
	G43BT	-	В					1				1				1				-				
	G43SA	-	В									1				i.				1				
	G43SAT1	-	В					1				1				1				1				
金属皮膜	GF063P	-	В																	1				
トリマポテンショメータ	GF063P1	-	В																	1				
	GF063P1T2	-	В																	1				
Cermet trimmers	GF063W	-	В																	1				
	GF063S	-	В																					
	GF063X	-	В																	1				
	GF063X1	-	В																	1				
	GF063U	-	В																	-				
	GF063UT2	-	В																	1				
	RJC06P	-	В	• •																1)
	RJC06W	-	В		• •															1)
	G12P	-	В																	1)
	G12X	-	В																	1)
	G12S	-	В																	1)
	GF121P	10S	В																	1				
	GF121P	5S	В																	1				

■標準在庫品一覧表 Stocked Standard Model